

NuxGATE

SIP/A16



NuxGATE SIP/A16 ofrece 16 puertos FXS para conectar TDM basada en la infraestructura de telefonía de red IP. NuxGATE SIP/A16 facilita la comunicación para las PMYES con una solución rentable y fiable.

Detalles

- Hasta 16 puertos FXS / FXO
- Hasta 6 canales GSM / CDMA / 3G
- Compatible con SIP e IAX2
- Hasta 2 puertos E1
- Rendimiento de fax fiable con T.38
- Totalmente compatible con SIP e IAX2
- GUI basada en web para fácil configuración y administración
- Excelente interoperabilidad con una amplia gama de equipos tradicionales e IP

	SIP/A4	SIP/A8	SIP/A16
Max Analog Ports	4	8	16
Max BRI Ports	4	8	16
Max GSM/3G Ports	1	4	6
VoIP Trunks	20	50	100
Protocol	SIP (RFC3261), IAX2		
Transport Protocol	UDP, TCP, TLS, SRTP		
Codec	G711 (alaw/ulaw), G722, G726, G729A, GSM, Speex, ADPCM, iLBC, H263, H263P, H264, MPEG4		
DTMF	In-band, RFC4733, RFC2833, SIP INFO		
LAN	1 × 10/100 Mbps	1 × 10/100/1000 Mbps	
WAN	1 × 10/100 Mbps	1 × 10/100/1000 Mbps	
IP Services	Static IP, DHCP, VPN, Firewall, VLAN, DDNS, PPPoE, QoS, Static NAT, STUN		
Firewall	Yes	Yes	Yes
T.38 Fax	Yes	Yes	Yes
Hot Standby	Yes	Yes	Yes
External Storage	TF Card	SD Card	SD Card
CPU	Freescale ARM Cortex-A9 1GHz	Freescale ARM Cortex-A9 1GHz (Dual Core)	Freescale i.MX 1GHz ARM Cortex-A9 (Quad Core)
RAM	DDR3 512MB	DDR3 512MB	DDR3 512MB
FLASH	4GB	4GB	4GB
USB	–	–	1
Power	DC 12V 1A	AC 100-240V 50/60HZ 0.6A max	AC 100-240V 50/60HZ 1.8A max
Size (L x W x H) (cm)	16 x 16 x 3	34 x 21 x 4.4	44 x 25.2 x 4.4
Weight	0.3 kg	1.48 kg	2.5 kg
Power Consumption	1.8-10.6 W	2.1-18.5 W	5.5-41.2 W
Environment	Operation Range: 0°C to 40°C; Storage Range: -20°C to 65°C; Humidity: 10-90% non-condensing		
Mounting	Desktop & Wall-mount	1U Rack-mount	